

Conference- & Informationssystem 5 Conference Terminal with Interpreter Channel

SDC 3000 DC

Cat. No. 04867

Description

The SDC 3000 DC is an extremely easy-to-use conference terminal. It features a built-in loudspeaker and electret microphone, ensuring excellent sound reproduction throughout the entire conference room. The unit is controlled via the MIC key. By pressing this key, for example, the participant can activate the microphone or "apply" to take the floor. A red LED ring on the microphone indicates who is allowed to take the floor or who has applied for a comment. In Voting Mode, the unit's three keys are assigned yes/no/abstention.

A simple change in configuration at the SDC CU central unit is all that is needed to turn the delegate unit into a chairperson unit. Two control keys which are otherwise inactive will be assigned special functions.

The SDC 3000 DC features a switchable interpreter channel which can be listened to via the headphone socket. A total of 11 channels are available for translations. The language is chosen with the SELECT key, the headphone volume can be individually adjusted with the VOLUME key.



Features

- Conference terminal with built-in electret microphone and loudspeaker
- Gooseneck microphone with LED ring
- Microphone key with LED
- Terminal can be used as a delegate unit or – by altering the configuration – as a chairperson unit
- Voting function (yes/no/abstention)
- Headphone output with volume control
- Conference channel plus 11 interpreter channels available at the headphone output
- LC display for volume and selected channel

Technical data

Frequency response (microphone)	150.....14000 Hz
Pick-up pattern	cardioid
Headphone connector	3,5 mm mono (>= 32 Ohm)
Voltage	20.....33 V DC
Power consumption	3 W
Operating temperature	+5.....+50 °C
Dimensions	192 x 470 x 174 mm
Weight	600 g

Delivery includes

1 SDC 3000 DC conference terminal

Recommended Accessories

Cable, length 2m	SDC CBL 2	Cat. No.04883
Cable, length 3m	SDC CBL 3	Cat. No.05114
Cable, length 5m	SDC CBL 5	Cat. No.04884
Cable, length 10m	SDC CBL 10	Cat. No.04885
Cable, length 20m	SDC CBL 20	Cat. No.04886
Cable, length 80m	SDC CBL 80	Cat. No.05321